



SURESOFT® PELLETS WITH RUSTBUSTER®

PRODUCTION LOCATION

Lyons, Kansas

PRODUCT DESCRIPTION

Vacuum pan salt produced by industry standard solution mining and evaporation process. The salt is washed, filtered, dried, screened, pressed into pellets, admixed, and quality control tested.

Compass Minerals SureSoft® Pellets with Rustbuster® is manufactured in compliance with standards from the American Water Works Association and is certified by the National Sanitation Foundation under standard NSF/ANSI 60.

Chemical Analysis			Typical	Range
(Before Admix - 99.7% Confidence)				
Sodium Chloride	NaCl	(%)	99.87	99.80 – 99.94

TYPICAL SCREEN ANALYSIS

Retained and Cumulative (99.7% Confidence)

U.S.S Mesh	Tyler Mesh	Open. (In.)	Ret. %	Range %	Cum. %	Range %
4	4	0.187	96.0	93 – 100	96.0	92 – 100
Pan	Pan		4.0	0 – 8	100.0	

PHYSICAL PROPERTIES

Bulk Density 74 pounds per cubic foot

Approximate Pellet Dimensions

Length	(in)	1.00
Width	(in)	0.50
Depth	(in)	0.50

Product and Pallet Specifications	Bag 40 lb.
Pallet Layout (Layers X Units)	9 x 7
Units per Pallet	63
Weight per Pallet (lb.)	2610
Height per Pallet (in.)	38
Cubic Feet per Pallet	42.2
Pallet Size (in.)	48 x 40
Pallet Weight (lb.)	60
Product Dimensions (in.)	27 x 13 x
Length x width x depth	3
Cubic Feet per Bag	0.61

METHOD OF ANALYSIS

American Society for Testing and Materials Procedure E534. All other testing is from Compass Minerals' internal quality control procedures, which are available upon request.

Product Description and Codes	UPC code	Product Code
40 lb. poly bag	041482-312403	31240

ADMIXTURE

The Rustbuster® additive is added as an iron removal agent for water softener resin maintenance.

PACKAGE COLOR CODE: GREEN