

IceAway Max[™] Professional Grade Ice Melt

Product Data Sheet

Product Description

- Ice and snow melt the moment they come in contact with IceAway Max, which offers one of the lowest melting temperatures available. A powerful, self-initiating chemical reaction generates heat, so melting occurs even in exceptionally cold weather.
- Melts ice and snow down to -25°F/-32°C.

Physical Properties

Method of Analysis

control procedures.

Constituent

Calcium Chloride Pellets

Testing is from Compass Minerals internal quality

Chemical Analysis

(%)

CaCl₂

Typical

100.00

Specification

73 Min

Bulk Density - 50 lbs/ft³

Admixture

No Additives



Typical and specifications are based on the previous years historical data:

Typical Screen Data									
U.S.S. Mesh	Tyler Mesh	Open (Inches)	Typical Retained %						
4	4	0.187	0.00						
8	8	0.0937	74.30						
12	10	0.0666	23.30						
16	14	0.0464	2.30						
Pan	Pan								

Packaging						Palletization				
UPC Code	Product Code	New Product Code	Bag Size (Lbs.)	Cubic Feet per Bag (Ft ³)	Dimensions (L x W x D)	Bag Material	Units per Pallet	Dimensions (W" x L" x H")	Weight (Lbs.)	Pallet Pattern
073841-506505	50650		50	0.70	25 x 16.5 x 4.5	Poly	48	48 x 40 x 60	2515	8 x 6

Compass Minerals

9900 West 109th Street – Suite 100 Overland Park, Kansas 66210 Ph: 800-755-7258 Fax: 800-359-7258 This information is based on our present state of knowledge and is intended to provide general notes on the product(s) supplied by us and their uses. The information should not be construed as a specific property promise or guarantee of the product(s).